

## “Toffee Tape” - Rubber Resin Tape

### Product description

A pressure-sensitive rubber resin adhesive designed for bonding to "difficult" substrates, such as polythene & polypropylene.

Toffee Tape is widely used across all sectors including but not limited to :

- Joining polythene sheeting.
- Mounting lightweight items and making any product adhesive.
- Fixing signs, edgings and trims.
- Joining of sheets and damp proof membranes.
- Bonding aluminium & GRP roof skins in the commercial bodybuilding industry.
- Adhering insulation to walls.
- Fixing of floor materials (carpets/strips).
- Temporary tarpaulin repair.

Available in various thicknesses from 0.2mm to 2mm and widths to suit your application.

### Product advantages

- Clean, easy to use alternative to brush on adhesives.
- Very aggressive pressure sensitive adhesive.
- Non-hardening and permanently flexible.
- Excellent bond strength.
- No curing time required.
- Solvent free, therefore no fumes.
- Forms a strong waterproof bond.
- Well established product with long term proven success.
- Pre-formed to a choice of sizes.
- Versatile “instant stick” adhesive on a roll.

# AS75 TAPE

## Rubber Resin Tape

### Technical Specification

Description	Units	Nominal Value
<i>Specific Gravity</i>	g cm <sup>-3</sup>	0.98
<i>Softening Point (Ring and Ball)</i>	° C	85
<i>Cohesion</i>	N mm <sup>-2</sup>	0.6
<i>Service Temperature</i>	° C	0 - 40

#### **STANDARD PRESENTATION**

Roll length for a standard adhesive thickness

30m (0.4mm), 50m (0.2mm), 20m (1.0mm), 10m (2.0mm)

Roll width 12mm, 19mm, 25mm, 38mm, 50mm

Note: non-standard sizes, and lead times is available on request

#### **RECOMMENDATIONS**

It is recommended that this product is applied at temperatures over 10° C.

To aid the cutting of AS75, it is advisable to dip blades or scissors into water immediately prior to use

The rolls should be stored flat on their cut edges in the original packaging, until required for use.

The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes.

Service life will vary with conditions of use and is affected by climatic environment, but should not be less than one year from date of manufacture, if stored in a moderate climate and good conditions.

The data and details in this leaflet were correct and up-to-date at the time of printing and are intended to provide information on our products and their possible applications. This leaflet is not a specification and does not assure specific product characteristics or make reference to the suitability of the products for a definite application. Because Star Fasteners (UK) Ltd cannot anticipate or control every application, we strongly recommend testing of this product under individual application conditions.