



# Two-Piece HuckBolts®



## THE UNSHAKEABLE WORLD OF HUCK® FASTENING SYSTEMS



### BobTail®

Huck's swaged-on fastener with no break-off pintail. Corrosion resistant and installs with lightweight ergonomic tooling.

1/4" - 3/8", 1/2" - 1" and 12mm - 20mm

Steel, Aluminum, Stainless

Grade 2, Grade 5 (Class 8.8), Grade 8 (Class 10.9)



### C50L®

Superior vibration resistance and durability for heavy-duty applications. Meets or exceeds all ASTM A-325 standards for shear, tensile and fatigue life.

1/2" - 1-3/8"

Steel, Aluminum, Stainless

Grade 5 (Class 8.8), Grade 8 (Class 10.9)



### C6L®/C120L/C150L

The classic 6-groove locking fastener ideal for a wide range of applications. Available in grades 2, 5, and 8.

3/16" - 3/8"

Steel, Aluminum, Stainless, Steel Pin with Stainless Head

Grade 2, Grade 5 (Class 8.8), Grade 8 (Class 10.9)



### Hucktainer®

Panel fastener that installs with consistent pressure, reducing crushing or crazing.

3/8"

Steel



### Magna-Grip®

Vibration-resistant, reliable grade 2 fasteners offering high uniform installed values with a wide grip range.

3/16" - 3/8"

Steel, Aluminum

### HUCK LOCKBOLTS

Huck LockBolts consist of two parts: a pin, and a collar. The bolt is inserted into one side of the joint material and the collar is placed over the bolt from the other side of the joint material. Access to both sides of the joint is required. A Huck installation tool is used to swage the collar materials into the grooves of the bolt providing a permanent and vibration resistant fastening.





# Huck® Structural Blind

FASTENERS THAT YOU NEVER HAVE TO THINK ABOUT



## Auto-Bulb®

Features a tapered lead-in point for automated, high-speed assemblies. Forms a bulb directly on the sheet line, preventing pull-through. Available in stainless steel.

3/16", 1/4"

Steel, Stainless Steel

Protruding, Countersunk



## BOM®

Blind, Oversize, Mechanically locked fasteners. Unique push-&-pull installation design for ultimate locking strength from blind-side install.

3/16" – 3/4"

Steel



## FloorTight®

Self-countersinking design for consistent installations in plywood and plymetal vehicle floor applications.

1/4", 5/16"

Steel

Standard, Wide Flange, Plymetal, 90° Countersunk



## HuckLok®

Wide 1/4" grip range, double-locking action clamps assembly from both sides for maximum joint integrity.

3/16", 1/4"

Steel

Protruding, Truss, 100° Oval Countersunk



## Magna-Bulb®

Unique bulbing fastener with high shear strength offers a broader bearing surface for high pull-out strength in thin materials and/or oversized holes.

3/16", 1/4", 5/16"

Steel

Protruding, Truss, 100° Oval Countersunk



## Magna-Lok®

Hole-filling fastener with excellent gap pull-out and moisture resistance. Solid circle lock creates internal lock that virtually eliminates pin push-out. Now available in 1/2" and 3/16" Stainless Steel.

3/16", 1/4", 3/8", 1/2"

Steel, Aluminum, Stainless Steel, 316 Stainless Steel

Protruding, Truss, 100° Flush



## Magna-Tite®

Has water-resistant sealant, for oversize holes and repairs. Large blind-side footprint for use in thin or low-strength materials.

3/16", 1/4"

Aluminum

Protruding, Shavable, Low Profile, 100° Oval Countersunk



## Penta-Lok™

Specially Designed for joining lightweight panels to steel, stainless steel and aluminium extrusion. No through hole required in the lightweight panel. High pin retention, with flush pin-break.

1/4"

Steel

Protruding

## BLIND FASTENERS

The pre-assembled, one-piece Huck blind fasteners are designed to be used in applications when access from only one side of the joint material is available. Installation is typically complete in 1 second and provides a secure, maintenance free joint.

